

## Power Supply/Read-out Unit for MFC RP-300



### ■ Outlines

- RP-300: Read-out unit intergrated with power supply, setting, and display needed to operate both the mass flow controller and mass flow meter

### ■ Features

- Wide range of rated voltage between AC100~245V
- Externally controllable
- Lockable switch to avoid operation errors
- Integrated operation from front panel
- Flexible scaling

CE RoHS

## Inline Monitor IM-10



### ■ Outlines

- IM-10: Device used to monitor the operation states of both mass flow controller and mass flow meter

### ■ Features

- Confirmation of the inlet/outlet voltage signals can be made during normal operating condition of mass flow controller and mass flow meter
- Signal displayed on LCD monitor
- External power supply not required due to bus-power operation

## Temperature Control Unit TCU Series



### ■ Outlines

- TCU Series: Temperature control unit for vaporizer, heat exchanger, supplying tank, and pipe heater

### ■ Features

- Electric thermoregulator and SSR integrated
- Auto power-off function when unusual rise in temperature is detected

RoHS

Model	TCU-3-1	TCU-3-2	TCU-3-2S
Temperature control	1 system	2 independent systems	2 interconnected systems
Rated voltage	AC100-200V 50/60Hz		
Maximum power consumption	33VA	40VA	
Operating temperature range	0 ~ 50°C 25 ~ 70% RH		
Weight	3.5kg	3.7kg	